

Systems

	EXP-C 24	EXP-C 36	EXP-C 54
PROFILES	NONE THERMAL	THERMAL BREAK	THERMAL BREAK
LEAF WEIGHT	300 KG	600 KG	1000 KG
LEAF HEIGHT	5 METER	5 METER	6 METER
LEAF AREA	10 M2	12 M2	18 M2
GLASS THICKNESS UP TO	24 MM	36 MM	54 MM
MEETING STILE WIDTH	18 MM	21.1 MM	21.1 MM
CONCEALED MULTI TRACK	YES	YES	YES
MULTI POINT LOCKING SYSTEMS	YES	YES	YES
AUTOMATIC SLIDING MOTORS	YES	YES	YES
AIR INFILTRATION & PERMEABILITY	CLASSE 4 (CLASS 4) (EN 12 207:2000)	CLASSE 4 (CLASS 4) (EN 12 207:2000)	CLASSE 4 (CLASS 4) (EN 12 207:2000)
WATER TIGHTNESS	CLASSE 7A (CLASS 7A) (EN 12 208:2000)	CLASSE 7A (CLASS 7A) (EN 12 208:2000)	CLASSE 7A (CLASS 7A) (EN 12 208:2000)
WIND RESISTANCE	CLASSE B4 (CLASS B4) (EN 12 210:2000)	CLASSE B4 (CLASS B4) (EN 12 210:2000)	CLASSE B4 (CLASS B4) (EN 12 210:2000)
THERMAL TRANSMITTANCE	N/A	1,0 - 1,7 (W/M ² K) (UNE-ISO 13947:2005)	0,8 - 1,2 (W/M ² K) (UNE-ISO 13947:2005)
ACOUSTIC INSULATION	UP TO 41 DB (NP EN 14351-1:2008 - ANEXO B)	UP TO 41 DB (NP EN 14351-1:2008 - ANEXO B)	UP TO 41 DB (NP EN 14351-1:2008 - ANEXO B)